

MODIFYING THE PRESCRIPTION DEFAULT VALUES

The Prescription Dialog is shown below with arrows drawn to show what tables are associated with the dialog lists. The SQL commands used to initialize the tables with the values is provided.

Rx	Disp	Sig
Ibuprofen, Oral 250mg	#30	As Needed
Ibuprofen, Oral	#15	Once a day
Ibuprofen, Oral 100mg	#30	Two times daily
Ibuprofen, Oral 250mg		Three times daily
Ibuprofen, Oral 500mg		Four times daily
Ibuprofen, Oral 800mg		

MedicineRx
Table

MedicineDisp
Table

MedicineSig
Table

```

INSERT INTO Medicine_Rx (FK_MED_TYPE_KEY,Rx ) VALUES (1,'100mg');
INSERT INTO Medicine_Rx (FK_MED_TYPE_KEY,Rx ) VALUES (1,'250mg');
INSERT INTO Medicine_Rx (FK_MED_TYPE_KEY,Rx ) VALUES (1,'500mg');
INSERT INTO Medicine_Rx (FK_MED_TYPE_KEY,Rx ) VALUES (1,'800mg');

INSERT INTO Medicine_Dispatch (FK_MED_TYPE_KEY,Disp ) VALUES (1,'#15');
INSERT INTO Medicine_Dispatch (FK_MED_TYPE_KEY,Disp ) VALUES (1,'#30');

INSERT INTO Medicine_Signature (FK_MED_TYPE_KEY,Sig ) VALUES (1,'Once a day');
INSERT INTO Medicine_Signature (FK_MED_TYPE_KEY,Sig ) VALUES (1,'Two times daily');
INSERT INTO Medicine_Signature (FK_MED_TYPE_KEY,Sig ) VALUES (1,'Three times daily');
INSERT INTO Medicine_Signature (FK_MED_TYPE_KEY,Sig ) VALUES (1,'Four times daily');
    
```